

1	2	3	4	5	6	7	A																														
							A																														
							B																														
							C																														
							D																														
<p>PIN OUT</p> <table border="1"> <tr> <th>P1</th> <th>COLOR</th> <th>P2</th> </tr> <tr> <td>1</td> <td>WHITE</td> <td>1</td> </tr> <tr> <td>2</td> <td>ORANGE</td> <td>2</td> </tr> <tr> <td>3</td> <td>WHITE</td> <td>3</td> </tr> <tr> <td>4</td> <td>GREEN</td> <td>4</td> </tr> <tr> <td>5</td> <td>BLUE</td> <td>5</td> </tr> <tr> <td>6</td> <td>WHITE</td> <td>6</td> </tr> <tr> <td>7</td> <td>WHITE</td> <td>7</td> </tr> <tr> <td>8</td> <td>BROWN</td> <td>8</td> </tr> <tr> <td>SHELL</td> <td>BRAID</td> <td>SHELL</td> </tr> </table>							P1	COLOR	P2	1	WHITE	1	2	ORANGE	2	3	WHITE	3	4	GREEN	4	5	BLUE	5	6	WHITE	6	7	WHITE	7	8	BROWN	8	SHELL	BRAID	SHELL	E
P1	COLOR	P2																																			
1	WHITE	1																																			
2	ORANGE	2																																			
3	WHITE	3																																			
4	GREEN	4																																			
5	BLUE	5																																			
6	WHITE	6																																			
7	WHITE	7																																			
8	BROWN	8																																			
SHELL	BRAID	SHELL																																			
<p>TEST CONDITION:</p> <ol style="list-style-type: none"> 100% OPEN & SHORT TESTING VOLTAGE: 300V DC INSULATION RESISTANCE: 10M ohm CONTACT RESISTANCE: 3 ohm (1M-3M) 5 ohm (5M-10M) 8 ohm (15M) 							F																														
<table border="1"> <thead> <tr> <th>NO.</th> <th>NAME</th> <th>DESCRIPTION</th> <th>QTY</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>④</td> <td>AL-FOIL</td> <td>Conductive AL-FOIL: W=8mm L=28mm</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>③</td> <td>OVERMOLD</td> <td>75A PVC Color: see order code</td> <td>N/A</td> <td>G</td> </tr> <tr> <td>②</td> <td>CONNECT</td> <td>CAT 6 RJ45 8P8C PLUG Brass 3u" gold, Shell: Nickel plated</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>①</td> <td>CABLE</td> <td>LAN CAT6 SSTP (24AWG*1P+AL)*4-BRAID, OD: 6.0±0.3mm JACKET COLOR: see order code</td> <td>1</td> <td>PCS</td> </tr> </tbody> </table>							NO.	NAME	DESCRIPTION	QTY	UNIT	④	AL-FOIL	Conductive AL-FOIL: W=8mm L=28mm	2	PCS	③	OVERMOLD	75A PVC Color: see order code	N/A	G	②	CONNECT	CAT 6 RJ45 8P8C PLUG Brass 3u" gold, Shell: Nickel plated	2	PCS	①	CABLE	LAN CAT6 SSTP (24AWG*1P+AL)*4-BRAID, OD: 6.0±0.3mm JACKET COLOR: see order code	1	PCS	G					
NO.	NAME	DESCRIPTION	QTY	UNIT																																	
④	AL-FOIL	Conductive AL-FOIL: W=8mm L=28mm	2	PCS																																	
③	OVERMOLD	75A PVC Color: see order code	N/A	G																																	
②	CONNECT	CAT 6 RJ45 8P8C PLUG Brass 3u" gold, Shell: Nickel plated	2	PCS																																	
①	CABLE	LAN CAT6 SSTP (24AWG*1P+AL)*4-BRAID, OD: 6.0±0.3mm JACKET COLOR: see order code	1	PCS																																	
<p>WSW order code AMJS0909-xxxx-xxB-24</p> <p>Cable length Cable&Molding color</p> <p>0030: 0.3±0.015M BK: Black 0050: 0.5±0.02M RD: Red 0100: 1.0±0.03M YE: Yellow 0150: 1.5±0.03M GN: Green 0200: 2.0±0.05M GY: Grey 0300: 3.0±0.08M BU: Blue 0500: 5.0±0.15M WH: White 0700: 7.0±0.25M BN: Brown 1000: 10±0.30M 1500: 15±0.50M</p>							H																														
<p>Customer-No.</p> <p>ASSMANN WSW-No. AMJS0909-xxxx-xxB-24</p> <p>ASSMANN WSW-No. AMJS0909-xxxx-xxB-24</p> <p>ASSMANN WSW-No. AMJS0909-xxxx-xxB-24</p>							G																														
<p>Scale Free</p> <p>TOLERANCE</p> <p>DIM TOL</p> <p>Angle TOL</p>							H																														
<p>RoHS compliant Unit: mm</p>							H																														
1	2	3	4	5	6	7	H																														
<p>ASSMANN components</p>		<p>30.03.2017 Amy</p>		<p>30.03.2017 Amy</p>		<p>30.03.2017 Amy</p>																															
<p>Drawn</p>		<p>Approved</p>		<p>Approved</p>		<p>Approved</p>																															
<p>Id.</p>		<p>Modification</p>		<p>Date</p>		<p>Name</p>																															
<p>Angle</p>		<p>TOL</p>		<p>Id.</p>		<p>Modification</p>																															
<p>1</p>		<p>2</p>		<p>3</p>		<p>4</p>																															
<p>1</p>		<p>2</p>		<p>3</p>		<p>4</p>																															