






REV.	DESCRIPTION	DATE
A	RELEASE	2012.11.12

NOTES:  
 Insulator Material: PBT, UL 94V-0  
 Contact Plating: Flash Gold  
 Contact Material: Brass

Current Rating : 1A AC,DC  
 Contact Resistance: 20MΩ Max.  
 Dielectric Withstanding: AC 500V  
 Insulator Resistance: 1000MΩ Min.  
 Operating Temp.: -40°C~+105°C

NUMBER OF POSITIONS	DIMENSIONS	
	A	B
06	4.00	21.60
08	6.00	23.60
10	8.00	25.60
12	10.00	27.60
14	12.00	29.60
16	14.00	31.60
20	18.00	35.60
24	22.00	39.60
26	24.00	41.60
30	28.00	45.60
34	32.00	49.60
40	38.00	55.60
44	42.00	59.60
50	48.00	65.60
60	58.00	75.60



UNLESS TOLERANCE

GENERAL	ANGLE	DRAW BY
X. ± 0.30	X°. ± 3.0°	
.X ± 0.20	.X° ± 2.0°	DESIGN BY
.XX ± 0.15	.XX° ± 1.0°	CHECK BY
.XXX ± 0.08	.XXX ± 0.5°	APPROVE BY

SCALE: 1:1    SHEET: 1/1    UNIT: MM

**CnC Tech,LLC**

Part NO.: 3110-XX-002-11-00

DRAW NO.:    REV: A

