Ratings
Voltage: 300 V
Temperature: -25 ~ 80 °C
Flammability: VW-1

Conductor
Conductor count: 9
Gauge: 24 AWG 0.22 mm²
Material: tinned copper strands
Strand size: ∅0.16 x 11
Resistance at 20 °C: 94.2 Ω /km max

Insulator
Material: PVC
Color: white, black, red, yellow, blue, green, orange, purple, gray
Diameter: ∅1.2 ±0.10 mm
Nominal thickness: 0.28 mm
Resistance at 20 °C: 10 MΩ /km min

Filler
Material: cotton rope

Outer jacket
Material: PVC
Color: white
Diameter: ∅6 ±0.20 mm
Nominal thickness: 0.76 mm

Wire marking: E339579 UL AWM STYLE 2464 24 AWG 80°C 300V VW-1 - - - cUL AWM I/II A 80°C 300V FT1 TENSILITY

Tests
Insulation tensile strength: 2.11 kgf/mm²
Jacket tensile strength: 1.05 kgf/mm²
After aging at 113 ±2 °C for 7 days:
Minimum tensile strength 70 % original
Minimum elongation 65 % original
Heat shock: 121 ±1 °C /1 hour, no observed degradation
Deformation: 121 ±1 °C /1 hour, ≤ 50 %
Cold bend: -10 ±2 °C /1 hour, no observed cracking



Revision:	Date:	Description:
A	10/13/2015	Initial release
A1	1/26/2016	Updated stranding
A2	8/17/2018	Increased operating temperature range

Prepared: AG Digitally signed by AG Date: 2018.09.06 14:58:53 -07'00'

Verified: CH Digitally signed by CH Date: 2018.09.06 15:04:12 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS and REACH compliant

Function test: no open, no short circuit, no intermittent

Description:
Wire, 9C TS, 24 AWG, UL2464, 300V, 80C, 6.0 mm, VW-1, PVC, white

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A
Part number: 30-00526
Scale: 10:1
Sheet 1 of 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com

5 4 3 2 1