



## #2200 Irradiated PVC Hook-Up Wire

UL Style 1429 · VW-1  
XLPVC MIL-W-16878 · TYPE B · 600V

**Description:** One conductor, tinned copper with .010" irradiated PVC insulation (XLPVC). Daburn's irradiated PVC Hook-up wire is made from extruded polyvinyl chloride insulation which has been exposed to controlled radiation. This exposure causes the insulation to become far superior to ordinary PVC in temperature, abrasion and cut-through resistance. It can withstand direct contact with a soldering iron and it will not shrink back, melt or deform. Ideal for hi-density wiring.

**Temperature Rating:** -55°C to +105°C (UL 1429: 80°C.)

**Voltage Rating:** Type B, 600V, (UL 1429: 150V).

This series is RoHS compliant.

DABURN Cat. No.	Size AWG	Strand	Nom. O.D.		Standard Packaging
			IN.	MM.	
2200/28	28	7/36	0.035	0.89	100', 1000'
2200/26	26	7/34	0.040	1.02	100', 1000'
2200/24	24	7/32	0.045	1.14	100', 1000'
2201/24	24	19/36	0.046	1.17	100', 1000'
2200/24S*	24	SOLID	0.041	1.04	100', 1000'
2201/22	22	19/34	0.052	1.32	100', 1000'
2200/22	22	7/30	0.051	1.30	100', 1000'
2200/22S*	22	SOLID	0.046	1.17	100', 1000'
2201/20	20	19/32	0.059	1.50	100', 1000'
2200/20	20	7/28	0.060	1.52	100', 1000'
2200/20S*	20	SOLID	0.054	1.37	100', 1000'
2201/18	18	19/30	0.070	1.78	100', 1000'
2200/18	18	7/26	0.070	1.78	100', 1000'
2200/16	16	19/29	0.078	1.98	100', 1000'

**Standard Colors:** White, Black, Red, Green, Yellow, Blue, Brown, Orange, Gray, Violet. Additional colors, sizes and constructions to order. Additional mil spec constructions are available to MIL-W-16878/14, MIL-W-16878/15 and MIL-W-16878/16.

\* Not Mil Spec Approved.