GSC.3S.290.ND92Z





Image for illustrative purpose only

Summary

Request a quote

Catalog					
Jacket cable outside diameter [mm]	7.80 - 9.20 mm				
Size	3S				
Series	S - Indoor Stepped Insert				

Technical details

Electrical Configuration

•					
Insert configuration value	3S.290 - no contacts				
Form & Material					
Shell style / Model id	GSC - Lead through with cable collet				
Housing material	Brass (nickel plated [SAE AMS QQ N 290]) collet and crimping tube, brass (chrome plated [SAE AMS 2460]) collet nut				
Keying	No keying				
Colour	Grey				
Weight	22.2 g				
Environment					
Technical domain	Audio Video, Energy and Industrial, Semiconductor, Test and Measurement				
Environmental sealing (IP rating)	No IP rating				
Temperature range	-55°C / +250°C				
Climatical Category	50/175/21				
Humidity (max)	<=95% [at 60 deg C /140 F]				
Shielding (min)	75 dB (10 MHz)				
Shielding (min)	40 dB (1 GHz)				
Shock Resistance	100 g [6 ms]				
Vibration	15 g [10 Hz - 2000 Hz]				
Salt Spray Corrosion	>144 hr				
Cable fixation					
Jacket cable outside diameter [mm]	7.80 - 9.20 mm				

Drawings



No keying

 $\underline{https://www.lemo.com/int_en/solutions/originals/s-indoor-stepped-insert/gsc-3s-290-nd92z.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMC components.

Dimensions

	Α	В	е	E	L	М	S2	S3	
mm.	17	19.5	M15x1.0	8.1	30	12	14	17	
in.	0.67	0.77		0.32	1.18	0.47	0.55	0.67	