ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00525	Connector, dc plug, 5.5x2.5xL18.5 mm, molding style, spring contacts, white insulators	1	
2	30-00396	Wire, 2C TS, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A, white	1	
3	24-00006	Overmold, PVC, white	1	



Notes:
Cables individually tied and bundled in groups of 10

Functionally equivalent components may be substituted

7 A, 48 Vdc

Wiring Diagram	
50-00525	wire color
center	white with stripe
sleeve	white

Revision:	Date:	Description:
A	10/30/2014	Initial release

Prepared: AL Digitally signed by AL Date: 2024.06.19 16:26:43 -07'00'

Verified: LV Digitally signed by LV Date: 2024.06.20 09:33:49 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Cable, 1830 mm, 5.5x2.5x10 mm 90° 50-00525 dc plug to stripped tinned, 18 AWG, 30-00396 wire, white

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A

Part number: 10-01245

Scale: 1:2

Sheet 1 of 1

5 4 3 2 1