



Image for illustrative purpose only

Summary

Request a quote

Catalog

Size

1M

Series

M - Rugged Ratchet coupling

https://www.lemo.com/int_en/solutions/optima/m-ratchet-coupling/bgf-1m-100-xav.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details


| Form | & | Materia | |
|------|---|---------|--|

| Shell style / Model id | BGF - Blanking cap for plugs (arctic grip) | | | | |
|-----------------------------------|---|--|--|--|--|
| Housing material | Aluminium (nickel plated [SAE AMS QQ N 290], anthracite color) shell and nut, other pieces bronze/brass | | | | |
| Keying | 3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts) | | | | |
| Colour | Grey | | | | |
| Weight | 7.14 g | | | | |
| Environment | | | | | |
| Technical domain | Motorsport, Security and Defence, Transportation, Aerospace and UAV | | | | |
| Environmental sealing (IP rating) | IP68 | | | | |
| Temperature range | -15°C / +135°C | | | | |
| EMI Shielding EIA 364-66A | >= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz) >= 40 dB (10 GHz) | | | | |
| Gunfire vibration | 25 Hz - 2000 Hz, 3 axis (Apache helicopter) | | | | |
| Humidity (max) | 21 days at 95% | | | | |
| Lighting strike EIA 364-76 | 10K amps - 6 times | | | | |
| Shock Resistance | 300 g [3 ms] | | | | |
| Thermal shock | 5 cycles: -65°C to +150°C | | | | |
| Vibration-Random | 37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz] | | | | |
| Vibration-Sine | 30 g, 3 axes, 12 hr [10 Hz - 2000 Hz] | | | | |
| Salt Spray Corrosion | max. 48 hr | | | | |

Drawings

https://www.lemo.com/int_en/solutions/optima/m-ratchet-coupling/bgf-1m-100-xav.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.



Dimensions

| | Α | С | L | Ν | Ρ | X | |
|-----|------|------|------|------|------|------|--|
| mm. | 15.9 | 14.2 | 24.6 | 85 | 5.3 | 6 | |
| in. | 0.63 | 0.56 | 0.97 | 3.35 | 0.21 | 0.24 | |

https://www.lemo.com/int_en/solutions/optima/m-ratchet-coupling/bgf-1m-100-xav.html LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them,