### **BME.3M.200.XAZ**





Image for illustrative purpose only

## **Summary**


| Request a quote |                             |
|-----------------|-----------------------------|
| Catalog         |                             |
|                 |                             |
| Size            | 3M                          |
| Series          | M - Rugged Ratchet coupling |

### **Technical details**

#### Form & Material

| Shell style / Model id            | BME - Blanking cap for fixed receptacle(knurled grip)  Aluminium (nickel plated [SAE AMS QQ N 290], anthracite color) shell and nut, other pieces bronze/brass |  |  |  |
|-----------------------------------|--|--|--|--|
| Housing material                  |  |  |  |  |
| Keying                            | 3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts)  |  |  |  |
| Colour                            | Grey   |  |  |  |
| Weight                            | 7.62 g   |  |  |  |
| Environment                       |  |  |  |  |
| Technical domain                  | Motorsport, Security and Defence, Transportation, Aerospace and UAV  |  |  |  |
| Environmental sealing (IP rating) | IP68   |  |  |  |
| Temperature range                 | -55°C / +135°C   |  |  |  |
| EMI Shielding EIA 364-66A         | >= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)   |  |  |  |
| Gunfire vibration                 | 25 Hz - 2000 Hz, 3 axis (Apache helicopter)  |  |  |  |
| Humidity (max)                    | 21 days at 95%   |  |  |  |
| Lighting strike EIA 364-76        | 10K amps - 6 times   |  |  |  |
| Shock Resistance                  | 300 g [ 3 ms]  |  |  |  |
| Thermal shock                     | 5 cycles: -65°C to +150°C  |  |  |  |
| Vibration-Random                  | 37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]  |  |  |  |
| Vibration-Sine                    | 30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]  |  |  |  |
| Salt Spray Corrosion              | max. 48 hr   |  |  |  |

# **Drawings**



### **Dimensions**

|     | A    | С    | L    | N    | Р    | X    |  |
|-----|------|------|------|------|------|------|--|
| mm. | 19.6 | 19.2 | 23.4 | 120  | 3.9  | 6    |  |
| in. | 0.77 | 0.76 | 0.92 | 4.72 | 0.15 | 0.24 |  |