## **BMF.3M.100.XAV**





Image for illustrative purpose only

## **Summary**


Request a quote		
Catalog		
Size	3M	
Series	M - Rugged Ratchet coupling	

## **Technical details**

#### Form & Material

Shell style / Model id	BMF - Blanking cap for plugs (knurled grip)		
Housing material	Aluminium (nickel plated [SAE AMS QQ N 290], anthracite color) shell and nut, other pieces bronze/brass		
Keying	3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts)		
Colour	Grey		
Weight	9.55 g		
Environment			
Technical domain	Motorsport, Security and Defence, Transportation, Aerospace and UAV		
Environmental sealing (IP rating)	IP68		
Temperature range	-15°C / +135°C		
EMI Shielding EIA 364-66A	>= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)		
Gunfire vibration	25 Hz - 2000 Hz, 3 axis (Apache helicopter)		
Humidity (max)	21 days at 95%		
Lighting strike EIA 364-76	10K amps - 6 times		
Shock Resistance	300 g [ 3 ms]		
Thermal shock	5 cycles: -65°C to +150°C		
Vibration-Random	37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]		
Vibration-Sine	30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]		
Salt Spray Corrosion	max. 48 hr		

# **Drawings**



### **Dimensions**

	Α	С	L	N	Р	X
mm.	19.6	19.2	24.6	120	5.3	6
in.	0.77	0.76	0.97	4.72	0.21	0.24