



Image for illustrative purpose only

## Summary

[Request a quote](#)

[Catalog](#)

|                                    |   |
|------------------------------------|---|
| Nb of contacts Triax               | 1   |
| Socket / Receptacle                | Socket / Receptacle - Fixed Panel Front Mounted |
| Locking system                     | Push-pull                                       |
| Jacket cable outside diameter [mm] | 1.30 - 18.60 mm                                 |
| Size                               | 2E  |
| Suggested matching part            | <a href="#">FFA.2E.675.CLAC40</a>               |
| Series                             | E - Outdoor Stepped Insert                      |

[https://www.lemo.com/int\\_en/solutions/originals/e-outdoor-stepped-insert/era-2e-675-ctl.html](https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/era-2e-675-ctl.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Electrical Configuration

|                            |   |
|----------------------------|---|
| Nb of contacts Triax       | 1   |
| Contact Termination Triax  | Solder  |
| Insert configuration value | 2E.675 - 1 Triax (75 Ohm)                                     |
| Insulator                  | T: PTFE   |
| Rated current              | 6 A   |
| Impedance                  | 75 Ohm  |
| OHM                        | 75  |
| VSWR                       | 1.02 + 0.07 * f/GHz   |
| Vtest                      | 1200 V (AC), 1690 V (DC)                                      |
| Contact Type               | Triaxial 75 Ohm (Solder)                                      |
| Cable type                 | Belden 8215,8232A,HF-2426,Triax 8 Nokia,375 029 LEDE, RGT 179 |
| Contact Dia.               | 0.9 mm (0.035in)  |

## Form & Material

|                        |  |
|------------------------|--|
| Shell style / Model id | ERA - Fixed receptacle, nut fixing   |
| Socket / Receptacle    | Fixed Panel Front Mounted  |
| Housing material       | Brass (chrome plated [SAE AMS 2460]) shell, collet nut and latch sleeve, nickel plated [SAE AMS QQ N 290] brass mid pieces |
| Locking system         | Push-pull  |
| Keying                 | Circular, female   |
| Colour                 | Grey   |
| Weight                 | 36.75 g  |

[https://www.lemo.com/int\\_en/solutions/originals/e-outdoor-stepped-insert/era-2e-675-ctl.html](https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/era-2e-675-ctl.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


## Environment

|                                   |   |
|-----------------------------------|---|
| Technical domain                  | Energy and Industrial, Test and Measurement |
| Environmental sealing (IP rating) | IP68  |
| Endurance                         | 5000 mating cycles                          |
| Temperature range                 | -55°C / +200°C                              |
| Climatical Category               | 50/175/21                                   |
| Humidity (max)                    | <=95% [at 60 deg C /140 F]                  |
| Shielding (min)                   | 95 dB (10 MHz)                              |
| Shielding (min)                   | 80 dB (1 GHz)                               |
| Shock Resistance                  | 100 g [ 6 ms]                               |
| Vibration                         | 15 g [10 Hz - 2000 Hz]                      |
| Salt Spray Corrosion              | >1000 hr                                    |

## Cable fixation

|                                    |                 |
|------------------------------------|-----------------|
| Jacket cable outside diameter [mm] | 1.30 - 18.60 mm |
|------------------------------------|-----------------|

## Drawings



## Dimensions

|     | A    | B    | e       | E    | L    | M   | S1   | S3   |
|-----|------|------|---------|------|------|-----|------|------|
| mm. | 25   | 27.5 | M20x1.0 | 9    | 28.5 | 5   | 18.5 | 24   |
| in. | 0.98 | 1.08 |         | 0.35 | 1.12 | 0.2 | 0.73 | 0.94 |

## Recommended By Lemo

### Accessories

|                |                                |
|----------------|--------------------------------|
| Compatible cap | <a href="#">BRE.2K.200.NAS</a> |
|----------------|--------------------------------|

[https://www.lemo.com/int\\_en/solutions/originals/e-outdoor-stepped-insert/era-2e-675-ctl.html](https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/era-2e-675-ctl.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.