PCA.0A.250.NTLC29





Image for illustrative purpose only

Summary

Request a quote


Catalog		
Nb of contacts Coax	1	
Socket / Receptacle	Socket / Receptacle - Free	
Locking system	Push-pull	
Jacket cable outside diameter [mm]	2.50 - 2.80 mm	
Size	0A	
Suggested matching part	FFA.0A.250.NTAC29	

Technical details

Electrical Configuration

Licetifear configuration			
Nb of contacts Coax	1		
Contact Termination Coax	Solder		
Insert configuration value	0A.250 - 1 Coax (50 Ohm)		
ОНМ	50		
Contact Type	Coaxial 50 Ohm (Solder)		
Bucket Dia.	1.1		
Form & Material			
Shell style / Model id	PCA - Straight receptacle with cable collet		
Socket / Receptacle	Free		
Housing material	Brass (nickel plated [SAE AMS QQ N 290]) shell, collet nut, latch sleeve and mid pieces		
Locking system	Push-pull		
Keying	3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts)		
Colour	Grey		
Weight	8.88 g		
Environment			
Environmental sealing (IP rating)	IP50		
Endurance	5000 mating cycles		
Salt Spray Corrosion	>144 hr		
Cable fixation			
Cable termination protection	Standard back nut (no additional protection)		
Fixation type	Cable collet		
Jacket cable outside diameter [mm]	2.50 - 2.80 mm		

Drawings



Dimensions

	A	В	L	S2	S 3	S1
mm.	9	10	35	8.5	9	8
in.	0.35	0.39	1.38	0.33	0.35	0.31

Cables

Cable PartNumber	Material	Colour	Cable image
17420	PVC	Black	
17450	COPOLYMER	Black	
18700	PTFE	White	- 6
18800	PTFE	White	
31600	PTFE	Brown	
CCX.50.RG1.74-U25N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74U25N	PVC	Black	
CCX.50.RG1.88AU26B	PFA	White	
CCX.50.RG1.88AU26B	PTFE	White	
CCX.50.RG3.16BU26M	FEP	Brown	
CCX.50.RG3.16U28M	PTFE	Brown	
CCX.75.RG1.79BU26M	FEP	Brown	
CCX.75.RG1.87AU26B	PFA	White	
CCX.75.RG1.87AU27B	PTFE	White	- 6 -

$\underline{https://www.lemo.com/int_en/pca-0a-250-ntlc29.html}$