### FCZ.T7.675.CTA03C





**▼** *Image for illustrative purpose only* 

## **Summary**


Catalog	
Nb of contacts Triax	1
Plug	Plug - Fixed
Locking system	Push-pull
Size	Т7

## **Technical details**

#### **Electrical Configuration**

Nb of contacts Triax	1
Contact Termination Triax	Solder
Rated current	12 A
OHM	75
Contact Type	Solder
Form & Material	
Shell style / Model id	FCZ - Fixed plug, collet clamp, nut fixing
Plug	Fixed
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Locking system	Push-pull
Keying	Circular, male
Colour	Grey
Weight	101.6 g
Environment	
Environmental sealing (IP rating)	IP68
Endurance	5000 mating cycles
Temperature range	-55°C / +250°C
Humidity (max)	<=95% [at 60 deg C /140 F]
Shock Resistance	100 g [ 6 ms]
Vibration	15 g [10 Hz - 20000 Hz]
Salt Spray Corrosion	>1000 hr
Cable fixation	
Cable termination protection	Standard back nut (no additional protection)
Fixation type	Cable collet

# **Drawings**





### **Dimensions**

	A	E	L	М	<b>S2</b>	е
mm.	35	19.5	41.2	6	12	M28x1.0
in.	1.38	0.77	1.62	0.24	0.47	