



Image for illustrative purpose only

## Summary

[Request a quote](#)

[Catalog](#)

Nb of contacts Triax	1
Plug	Plug - Elbow
Locking system	Push-pull
Jacket cable outside diameter [mm]	3.80 - 4.40 mm
Suggested matching part	<a href="#">ERA.0S.650.CTA</a>
Series	S - Indoor Stepped Insert

[https://www.lemo.com/int\\_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html](https://www.lemo.com/int_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Electrical Configuration

Nb of contacts Triax	1
Contact Termination Triax	Solder
Insert configuration value	0S.650 - 1 Triax (50 Ohm)
Insulator	T: PTFE
Rated current	6 A
Impedance	50 Ohm
OHM	50
VSWR	$1.03 + 0.34 * f/\text{GHz}$
Vtest	1200 V (AC), 1700 V (DC)
Contact Type	Triaxial 50 Ohm (Solder)
Cable type	10369
Bucket Dia.	0.8
Contact Dia.	0.9 mm (0.035" in)

## Form & Material

Shell style / Model id	FLA - Elbow plug, cable collet and nut for fitting a bend relief
Plug	Elbow
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Locking system	Push-pull
Keying	Circular, female
Colour	Gray
Variant	Nut for fitting a bend relief
Weight	15.31 g

[https://www.lemo.com/int\\_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html](https://www.lemo.com/int_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


## Environment

Technical domain	Audio Video, Energy and Industrial, Semiconductor, Test and Measurement
Environmental sealing (IP rating)	IP50
Temperature range	-55°C / +250°C
Climatical Category	50/175/21
Humidity (max)	<=95% [at 60 deg C /140 F]
Shielding (min)	75 dB (10 MHz)
Shielding (min)	40 dB (1 GHz)
Shock Resistance	100 g [ 6 ms]
Vibration	15 g [10 Hz - 2000 Hz]
Salt Spray Corrosion	>144 hr

## Cable fixation

Cable termination protection	For cable bend relief
Fixation type	Cable collet
Jacket cable outside diameter [mm]	3.80 - 4.40 mm

## Drawings



## Dimensions

	A	L	M	S1	S2	H
mm.	13	23	13	8	6.5	24.5
in.	0.51	0.91	0.51	0.31	0.26	0.96

[https://www.lemo.com/int\\_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html](https://www.lemo.com/int_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Recommended By Lemo

## Accessories

---

Compatible cap

[BFG.0B.100.PCZG](#)

[https://www.lemo.com/int\\_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html](https://www.lemo.com/int_en/solutions/originals/s-indoor-stepped-insert/fla-0s-650-ctlc42z.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.