

RECOMMENDER PCB LAYOUT


Material

- ① Terminal body(Contact pin):Brass
- ② Wire guard: Stainless steel
- ③ Surface of solder tail: Tin plated
- ④ Insulator(housing): Thermoplastic (UL94V-0), GREEN(RAL6018/T)

Electrical

cULus/VDE  
 Voltage rating: 300VAC/450VAC  
 Current rating: 10A/10A  
 Wire range:0.75-1.5mm<sup>2</sup>  
 Solid wire(AWG): 14-24  
 Stranded wire(AWG): 14-24  
 Pull force:

Screw:  
 Wire strip length: 9-10mm  
 Withstanding Voltage: 1.6KV/2.5KV  
 Operating temperature: -40°C to +115°C  
 Soldering temperature: 250°C±10°C/5 Sec  
 Safety Approval:



DIMENSION

L	Nx7.5
P	(N-1)x7.5


N=Number of poles

Poles	Tolerance	DIM L	DIM P
2p-6p		±0.15	±0.10
7p-12p		±0.20	±0.20
13p-18p		±0.30	±0.25
19p-24p		±0.40	±0.30

Scale	Free	Date	Name
TOLERANCE		19.04.2010	Alex
X.	±0.50		
X.X	±0.30		
X.XX	±0.10	19.04.2016	Winnie
DIM	TOL		
X.°	±1°	16.04.2013	Amy
Angle	TOL	19.04.2010	Alex

Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace
	A-TB750-HAXXH	ASS 4126 CO	rev02
			Sheet

**RoHS compliant**



1	2	3	4	5	6	7
H	G	F	E	D	C	B