



P.C.B Layout

MATERIAL:
 HOUSING:PBT+30%G.F UL 94V-0
 CONTACT:BRASS T=0.25mm
 SHELL:SPCC T=0.30mm
 PLATING:
 CONTACT: GOLD AND TIN OVER NICKEL PLATING
 SHELL: NICKEL OVER ALL PLATING
 SPECIFICATION:
 CURRENT-MAX[AMPS]1.5A
 VOLTAGE-MAX[VOLTS]:30V
 WITHSTANDING VOLTAGE:500V AC
 CONTACT RESISTANCE[OHMS]:30mΩ MIN
 INSULATION RESISTANCE[OHMS]:1000MΩ MIN
 INSULATION COLOR:WHITE
 ENVIRONMENTAL:
 TEMPERATURE RANGE:-40°C TO+105°C

09/14-15	yang		NEW DWG		AO				
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.				
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参考表			<h1 style="text-align: center;">CnC Tech, LLC</h1> <p style="text-align: center;">TITLE: USB 4P AM SMT 贴片式成品</p>						
X.X	±0.38	X.X°				±3.00°	APPD:	PRODUCT NO: 1001-011-01101	
X.XX	±0.25	X.XX°	±2.00°	CHECK:	DATE	SCALE	UNIT	TYPE	PAGE
X.XXX	±0.10	X.XXX°	±1.00°	DRAW:	2015.09.09	1:1	mm	Z	1 / 1