

## Phase Control Thyristors (Hockey PUK Version), 910 A


**B-PUK (TO-200AC)**
**FEATURES**

- Center amplifying gate
- Metal case with ceramic insulator
- International standard case B-PUK (TO-200AC)
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS  
COMPLIANT**
**TYPICAL APPLICATIONS**

- DC motor controls
- Controlled DC power supplies
- AC controllers

| PRIMARY CHARACTERISTICS |                                |
|-------------------------|--------------------------------|
| $I_{T(AV)}$             | 910 A                          |
| $V_{DRM}/V_{RRM}$       | 1200 V, 1600 V, 1800 V, 2000 V |
| $V_{TM}$                | 1.80 V                         |
| $I_{GT}$                | 100 mA                         |
| $T_J$                   | -40 °C to +125 °C              |
| Package                 | B-PUK (TO-200AC)               |
| Circuit configuration   | Single SCR                     |

| MAJOR RATINGS AND CHARACTERISTICS |                 |              |                   |
|-----------------------------------|-----------------|--------------|-------------------|
| PARAMETER                         | TEST CONDITIONS | VALUES       | UNITS             |
| $I_{T(AV)}$                       |                 | 910          | A                 |
|                                   | $T_{hs}$        | 55           | °C                |
| $I_{T(RMS)}$                      |                 | 1857         | A                 |
|                                   | $T_{hs}$        | 25           | °C                |
| $I_{TSM}$                         | 50 Hz           | 15 700       | A                 |
|                                   | 60 Hz           | 16 400       |                   |
| $I^2t$                            | 50 Hz           | 1232         | kA <sup>2</sup> s |
|                                   | 60 Hz           | 1125         |                   |
| $V_{DRM}/V_{RRM}$                 |                 | 1200 to 2000 | V                 |
| $t_q$                             | Typical         | 150          | µs                |
| $T_J$                             |                 | -40 to 125   | °C                |

| VOLTAGE RATINGS |              |  |  |  |
|-----------------|--------------|--|--|--|
| TYPE NUMBER     | VOLTAGE CODE | $V_{DRM}/V_{RRM}$ , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE PEAK VOLTAGE<br>V | $I_{DRM}/I_{RRM}$ MAXIMUM AT $T_J = T_J$ MAXIMUM<br>mA |
| VS-ST700CL      | 12           | 1200   | 1300   | 80   |
|                 | 16           | 1600   | 1700   |  |
|                 | 18           | 1800   | 1900   |  |
|                 | 20           | 2000   | 2100   |  |



| <b>ABSOLUTE MAXIMUM RATINGS</b>                          |                |   |            |                           |                    |                   |
|--|----------------|---|------------|---------------------------|--------------------|-------------------|
| PARAMETER  | SYMBOL         | TEST CONDITIONS   |            | VALUES                    | UNITS              |                   |
| Maximum average on-state current at heatsink temperature | $I_{T(AV)}$    | 180° conduction, half sine wave double side (single side) cooled                        |            | 910 (355)                 | A                  |                   |
|  |                |   |            | 55 (85)                   | °C                 |                   |
| Maximum RMS on-state current                             | $I_{T(RMS)}$   | DC at 25 °C heatsink temperature double side cooled                                     |            | 1857                      |                    |                   |
| Maximum peak, one-cycle non-repetitive surge current     | $I_{TSM}$      | Sinusoidal half wave, initial $T_J = T_J$ maximum                                       | t = 10 ms  | No voltage reapplied      | 15 700             | A                 |
|  |                |   | t = 8.3 ms |                           | 16 400             |                   |
|  |                |   | t = 10 ms  | 100 % $V_{RRM}$ reapplied | 13 200             |                   |
|  |                |   | t = 8.3 ms |                           | 13 800             |                   |
| Maximum $I^2t$ for fusing                                | $I^2t$         |   | t = 10 ms  | No voltage reapplied      | 1232               | kA <sup>2</sup> s |
|  |                |   | t = 8.3 ms |                           | 1125               |                   |
|  |                |   | t = 10 ms  | 100 % $V_{RRM}$ reapplied | 871                |                   |
|  |                |   | t = 8.3 ms |                           | 795                |                   |
| Maximum $I^2\sqrt{t}$ for fusing                         | $I^2\sqrt{t}$  | t = 0.1 to 10 ms, no voltage reapplied  |            | 12 321                    | kA <sup>2</sup> /s |                   |
| Low level value of threshold voltage                     | $V_{T(TO)1}$   | (16.7 % $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$ , $T_J = T_J$ maximum) |            | 1.00                      | V                  |                   |
| High level value of threshold voltage                    | $V_{T(TO)2}$   | (I > $\pi \times I_{T(AV)}$ , $T_J = T_J$ maximum)                                      |            | 1.13                      |                    |                   |
| Low level value of on-state slope resistance             | $r_{\theta 1}$ | (16.7 % $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$ , $T_J = T_J$ maximum) |            | 0.40                      | mΩ                 |                   |
| High level value of on-state slope resistance            | $r_{\theta 2}$ | (I > $\pi \times I_{T(AV)}$ , $T_J = T_J$ maximum)                                      |            | 0.35                      |                    |                   |
| Maximum on-state voltage                                 | $V_{TM}$       | $I_{pk} = 2000$ A, $T_J = T_J$ maximum, $t_p = 10$ ms sine pulse                        |            | 1.80                      | V                  |                   |
| Maximum holding current                                  | $I_H$          | $T_J = 25$ °C, anode supply 12 V resistive load   |            | 600                       | mA                 |                   |
| Typical latching current                                 | $I_L$          |   |            | 1000                      |                    |                   |

| <b>SWITCHING</b>   |        |  |  |        |       |
|--|--------|--|--|--------|-------|
| PARAMETER  | SYMBOL | TEST CONDITIONS  |  | VALUES | UNITS |
| Maximum non-repetitive rate of rise of turned-on current | di/dt  | Gate drive 20 V, 20 Ω, $t_r \leq 1$ μs<br>$T_J = T_J$ maximum, anode voltage $\leq 80$ % $V_{DRM}$                       |  | 1000   | A/μs  |
| Typical delay time                                       | $t_d$  | Gate current 1 A, di/dt = 1 A/μs<br>$V_d = 0.67$ % $V_{DRM}$ , $T_J = 25$ °C   |  | 1.0    | μs    |
| Typical turn-off time                                    | $t_q$  | $I_{TM} = 750$ A, $T_J = T_J$ maximum, di/dt = 60 A/μs,<br>$V_R = 50$ V, dV/dt = 20 V/μs, gate 0 V 100 Ω, $t_p = 500$ μs |  | 150    |       |

| <b>BLOCKING</b>                                    |                          |  |  |        |       |
|--|--------------------------|--|--|--------|-------|
| PARAMETER  | SYMBOL                   | TEST CONDITIONS                                      |  | VALUES | UNITS |
| Maximum critical rate of rise of off-state voltage | dV/dt                    | $T_J = T_J$ maximum linear to 80 % rated $V_{DRM}$   |  | 500    | V/μs  |
| Maximum peak reverse and off-state leakage current | $I_{RRM}$ ,<br>$I_{DRM}$ | $T_J = T_J$ maximum, rated $V_{DRM}/V_{RRM}$ applied |  | 80     | mA    |



| <b>TRIGGERING</b>                   |             |  |                |      |       |    |
|-------------------------------------|-------------|--|----------------|------|-------|----|
| PARAMETER                           | SYMBOL      | TEST CONDITIONS  | VALUES         |      | UNITS |    |
|                                     |             |  | Typ.           | Max. |       |    |
| Maximum peak gate power             | $P_{GM}$    | $T_J = T_J$ maximum, $t_p \leq 5$ ms   | 10.0           |      | W     |    |
| Maximum average gate power          | $P_{G(AV)}$ | $T_J = T_J$ maximum, $f = 50$ Hz, $d\% = 50$   | 2.0            |      |       |    |
| Maximum peak positive gate current  | $I_{GM}$    | $T_J = T_J$ maximum, $t_p \leq 5$ ms   | 3.0            |      | A     |    |
| Maximum peak positive gate voltage  | $+V_{GM}$   | $T_J = T_J$ maximum, $t_p \leq 5$ ms   | 20             |      | V     |    |
| Maximum peak negative gate voltage  | $-V_{GM}$   |  | 5.0            |      |       |    |
| DC gate current required to trigger | $I_{GT}$    | Maximum required gate trigger/ current/voltage are the lowest value which will trigger all units 12 V anode to cathode applied | $T_J = -40$ °C | 200  | -     | mA |
|                                     |             |  | $T_J = 25$ °C  | 100  | 200   |    |
|                                     |             |  | $T_J = 125$ °C | 50   | -     |    |
| DC gate voltage required to trigger | $V_{GT}$    | Maximum required gate trigger/ current/voltage are the lowest value which will trigger all units 12 V anode to cathode applied | $T_J = -40$ °C | 2.5  | -     | V  |
|                                     |             |  | $T_J = 25$ °C  | 1.8  | 3.0   |    |
|                                     |             |  | $T_J = 125$ °C | 1.1  | -     |    |
| DC gate current not to trigger      | $I_{GD}$    | $T_J = T_J$ maximum  | 10             |      | mA    |    |
| DC gate voltage not to trigger      | $V_{GD}$    |  | 0.25           |      | V     |    |

| <b>THERMAL AND MECHANICAL SPECIFICATIONS</b>     |              |   |                  |           |
|--|--------------|---|------------------|-----------|
| PARAMETER  | SYMBOL       | TEST CONDITIONS                               | VALUES           | UNITS     |
| Maximum operating junction temperature range     | $T_J$        |   | -40 to 125       | °C        |
| Maximum storage temperature range                | $T_{Stg}$    |   | -40 to 150       |           |
| Maximum thermal resistance, junction to heatsink | $R_{thJ-hs}$ | DC operation single side cooled               | 0.073            | K/W       |
|  |              | DC operation double side cooled               | 0.031            |           |
| Maximum thermal resistance, case to heatsink     | $R_{thC-hs}$ | DC operation single side cooled               | 0.011            |           |
|  |              | DC operation double side cooled               | 0.006            |           |
| Mounting force, $\pm 10$ %                       |              |   | 14 700<br>(1500) | N<br>(kg) |
| Approximate weight                               |              |   | 255              | g         |
| Case style                                       |              | See dimensions - link at the end of datasheet | B-PUK (TO-200AC) |           |

| <b><math>\Delta R_{thJ-hs}</math> CONDUCTION</b> |                       |             |                        |             |                     |       |
|--|-----------------------|-------------|------------------------|-------------|---------------------|-------|
| CONDUCTION ANGLE                                 | SINUSOIDAL CONDUCTION |             | RECTANGULAR CONDUCTION |             | TEST CONDITIONS     | UNITS |
|  | SINGLE SIDE           | DOUBLE SIDE | SINGLE SIDE            | DOUBLE SIDE |                     |       |
| 180°   | 0.009                 | 0.009       | 0.006                  | 0.006       | $T_J = T_J$ maximum | K/W   |
| 120°   | 0.011                 | 0.011       | 0.011                  | 0.011       |                     |       |
| 90°  | 0.014                 | 0.014       | 0.015                  | 0.015       |                     |       |
| 60°  | 0.020                 | 0.020       | 0.021                  | 0.021       |                     |       |
| 30°  | 0.036                 | 0.036       | 0.036                  | 0.036       |                     |       |

**Note**

- The table above shows the increment of thermal resistance  $R_{thJ-hs}$  when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 5 - On-State Power Loss Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 6 - On-State Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current Single and Double Side Cooled



Fig. 8 - Maximum Non-Repetitive Surge Current Single and Double Side Cooled



Fig. 9 - On-State Voltage Drop Characteristics



Fig. 10 - Thermal Impedance  $Z_{thJ-hs}$  Characteristics



Fig. 11 - Gate Characteristics

**ORDERING INFORMATION TABLE**

|             |            |           |           |          |          |           |          |          |          |
|-------------|------------|-----------|-----------|----------|----------|-----------|----------|----------|----------|
| Device code | <b>VS-</b> | <b>ST</b> | <b>70</b> | <b>0</b> | <b>C</b> | <b>20</b> | <b>L</b> | <b>1</b> | <b>-</b> |
|             | (1)        | (2)       | (3)       | (4)      | (5)      | (6)       | (7)      | (8)      | (9)      |

- 1** - Vishay Semiconductors product
- 2** - Thyristor
- 3** - Essential part number
- 4** - 0 = converter grade
- 5** - C = ceramic PUK
- 6** - Voltage code x 100 =  $V_{RRM}$  (see Voltage Ratings table)
- 7** - L = PUK case B-PUK (TO-200AC)
- 8** - 0 = eyelet terminals (gate and auxiliary cathode unsoldered leads)  
 1 = fast-on terminals (gate and auxiliary cathode unsoldered leads)  
 2 = eyelet terminals (gate and auxiliary cathode soldered leads)  
 3 = fast-on terminals (gate and auxiliary cathode soldered leads)
- 9** - Critical dV/dt: • None = 500 V/μs (standard selection)  
 • L = 1000 V/μs (special selection)


| LINKS TO RELATED DOCUMENTS |  |
|----------------------------|--|
| Dimensions                 | <a href="http://www.vishay.com/doc?95076">www.vishay.com/doc?95076</a> |



## B-PUK (TO-200AC)

**DIMENSIONS** in millimeters (inches)

Creepage distance: 36.33 (1.430) minimum  
Strike distance: 17.43 (0.686) minimum



Quote between upper and lower pole pieces has to be considered after application of mounting force (see thermal and mechanical specification)



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.