

## FLARE-MINI-AD-PIN

~100° x 20° oval beam. Assembly with location pins and installation tape.

### SPECIFICATION:

Dimensions	Ø 16.0 mm
Height	9.1 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ




### MATERIALS:

Component	Type	Material	Colour	Finish	Length
FLARE-MINI-AD-PIN	Single lens	PMMA	clear		16.0
TINA-TAPE3	Tape	Acrylic foam	black		16.0

### ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA13058_FLARE-MINI-AD-PIN	Single lens	4600	230	230	6.9
» Box size:					




See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### OPTICAL RESULTS (MEASURED):




**LED** XB-D  
**FWHM / FWTM** 100.0 + 16.0° / 160.0 + 31.0°  
**Efficiency** 93 %  
**Peak intensity** 1.2 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**



Light distribution files




**LED** XP-E2  
**FWHM / FWTM** 90.0 + 16.0° / 150.0 + 30.0°  
**Efficiency** 94 %  
**Peak intensity** 1.4 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**



Light distribution files



**LED** XP-G  
**FWHM / FWTM** 100.0 + 20.0° / 156.0 + 34.0°  
**Efficiency** 94 %  
**Peak intensity** 1.1 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**




Light distribution files

#### OPTICAL RESULTS (MEASURED):





LED XP-G2  
 FWHM / FWTM 95.0 + 21.0° / 151.0 + 37.0°  
 Efficiency 94 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files





LED XP-G4  
 FWHM / FWTM 97.0 + 22.0° / 133.0 + 39.0°  
 Efficiency 94 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED XP-L HD  
 FWHM / FWTM 108.0 + 27.0° / 154.0 + 51.0°  
 Efficiency 92 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (MEASURED):




LED XP-L2  
 FWHM / FWTM 102.0 + 29.0° / 154.0 + 54.0°  
 Efficiency 94 %  
 Peak intensity 0.8 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED XT-E  
 FWHM / FWTM 104.0 + 19.0° / 164.0 + 36.0°  
 Efficiency 94 %  
 Peak intensity 1.1 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED LUXEON A  
 FWHM / FWTM 92.0 + 20.0° / 148.0 + 36.0°  
 Efficiency 94 %  
 Peak intensity 1.1 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (MEASURED):




**LED** LUXEON CZ  
**FWHM / FWTM** 102.0 + 12.0° / 146.0 + 25.0°  
**Efficiency** 94 %  
**Peak intensity** 1.8 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**



Light distribution files




**LED** NVSW219F  
**FWHM / FWTM** 100.0 + 24.0° / 149.0 + 42.0°  
**Efficiency** 94 %  
**Peak intensity** 1 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**



Light distribution files



**LED** NVSxx19A  
**FWHM / FWTM** 100.0 + 20.0° / 147.0 + 34.0°  
**Efficiency** 94 %  
**Peak intensity** 1.1 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**




Light distribution files

#### OPTICAL RESULTS (MEASURED):

**OSRAM**  
Opto Semiconductors


LED OSLON Square EC  
FWHM / FWTM 92.0 + 21.0° / 148.0 + 36.0°  
Efficiency 94 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**SAMSUNG**



LED LH351B  
FWHM / FWTM 101.0 + 24.0° / 142.0 + 40.0°  
Efficiency 94 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




**SAMSUNG**

LED LH351Z  
FWHM / FWTM 99.0 + 24.0° / 135.0 + 41.0°  
Efficiency 94 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

### OPTICAL RESULTS (MEASURED):






### OPTICAL RESULTS (SIMULATED):




LED XP-G3  
FWHM / FWTM 93.0 + 20.0° / 151.0 + 37.0°  
Efficiency 94 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED LUXEON C  
FWHM / FWTM 13.0 + 86.0° / 23.0 + 167.0°  
Efficiency 93 %  
Peak intensity 1.6 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED LUXEON Z ES  
FWHM / FWTM 90.0 + 14.0° / 144.0 + 26.0°  
Efficiency 96 %  
Peak intensity 1.7 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED OSLON Square CSSRM2/CSSRM3  
 FWHM / FWTM 88.0 + 18.0° / 142.0 + 32.0°  
 Efficiency 95 %  
 Peak intensity 1.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files

**SEOL**  
SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2  
 FWHM / FWTM 91.0 + 19.0° / 142.0 + 31.0°  
 Efficiency 95 %  
 Peak intensity 1.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)