



Molded, 50 mil Pitch, Dual-In-Line Thin Film Divider, Surface Mount Resistor Network



Vishay Dale Thin Film ORN series Dividers provide optimum ratio precision, small size and exceptional stability for most applications. They offer a wide ratio range that is listed in the selection guide and are available for immediate delivery. The tight ratio tolerance offered on the standard ratios will provide exceptional performance throughout life.

SCHEMATIC



FEATURES

- 0.068" (1.73 mm) maximum seated height
- Rugged molded case construction with no internal solder (JEDEC® MS-012 variation AA package)
- Low TCR tracking ± 5 ppm/°C
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS*
Available
HALOGEN FREE

Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details

TYPICAL PERFORMANCE

	ABSOLUTE	TRACKING
TCR	25	5
	ABSOLUTE	RATIO
TOL.	0.1	0.05

STANDARD RESISTANCE OFFERING (R₁/R₂)

RATIO	R ₁	R ₂
100:1	100K	1K
50:1	50K	1K
25:1	25K	1K
20:1	20K	1K
10:1	10K	1K
5:1	10K	2K
2:1	10K	5K

STANDARD ELECTRICAL SPECIFICATIONS

TEST	SPECIFICATIONS	CONDITIONS
Material	Passivated nichrome	-
Pin/Lead Number	8	-
Resistance Range	1000 Ω to 100 k Ω per resistor	-
TCR: Absolute	± 25 ppm/°C	-55 °C to +125 °C
TCR: Tracking	± 5 ppm/°C	-55 °C to +125 °C
Tolerance: Absolute	± 0.1 %	+25 °C
Tolerance: Ratio	± 0.05 %	+25 °C
Power Rating: Resistor	100 mW	Maximum at +70 °C
Power Rating: Package	400 mW	Maximum at +70 °C
Stability: Absolute	$\Delta R \pm 0.05$ %	2000 h at +70 °C
Stability: Ratio	$\Delta R \pm 0.015$ %	2000 h at +70 °C
Voltage Coefficient	< 0.1 ppm/V	-
Working Voltage	100 V max. not to exceed $\sqrt{P \times R}$	-
Operating Temperature Range	-55 °C to +125 °C	-
Storage Temperature Range	-55 °C to +150 °C	-
Noise	< -30 dB	-
Thermal EMF	0.08 μ V/°C	-
Shelf Life Stability: Absolute	$\Delta R \pm 0.01$ %	1 year at +25 °C
Shelf Life Stability: Ratio	$\Delta R \pm 0.002$ %	1 year at +25 °C

Note


- Tantalum nitride film is custom, consult factory

DIMENSIONS AND IMPRINTING in inches and millimeters			
	DIMENSION	INCHES	MILLIMETERS
	A	0.154 ± 0.003	3.90 ± 0.09
	B	0.016 ± 0.002	0.4 ± 0.06
	C	0.050	1.27
	D	0.193 ± 0.004	4.90 ± 0.1
	E	0.008 ± 0.001	0.20 ± 0.03
	F	0.032 ± 0.016	0.81 ± 0.4
	G	0.236 ± 0.008	6.00 ± 0.2
	H	0.068 max.	1.73
	I	0.007 ± 0.003	0.18 ± 0.07
Ø	2° to 6°	2° to 6°	

Note

- Marking - Vishay symbol, part number from ordering information

MECHANICAL SPECIFICATIONS	
Resistive Element	Passivated nichrome
Substrate Material	Silicon
Body	Molded epoxy
Terminals	Copper alloy
Lead (Pb)-free Option	100 % matte tin
Tin Lead Option	Sn90
Tin Lead and Lead (Pb)-free Finish	Plated



GLOBAL PART NUMBER INFORMATION																								
New Global Part Numbering: ORNA5-1UF																								
<table border="1"> <tr><td>O</td><td>R</td><td>N</td><td>A</td></tr> <tr><td>O</td><td>R</td><td>N</td><td>T</td><td>A</td></tr> </table>	O	R	N	A	O	R	N	T	A	<table border="1"> <tr><td>5</td><td>-</td><td>1</td></tr> <tr><td>1</td><td>0</td><td>0</td><td>-</td><td>1</td></tr> </table>	5	-	1	1	0	0	-	1	<table border="1"> <tr><td>U</td><td>F</td></tr> <tr><td>U</td><td>F</td></tr> </table>	U	F	U	F	
O	R	N	A																					
O	R	N	T	A																				
5	-	1																						
1	0	0	-	1																				
U	F																							
U	F																							
<table border="1"> <tr><td>GLOBAL MODEL (4 or 5 digits)</td></tr> <tr><td>ORNA (Tin/lead)</td></tr> <tr><td>ORNTA (Lead (Pb)-free) (e3)</td></tr> </table>	GLOBAL MODEL (4 or 5 digits)	ORNA (Tin/lead)	ORNTA (Lead (Pb)-free) (e3)	<table border="1"> <tr><td>RESISTANCE (3, 4 or 5 digits)</td></tr> <tr><td>2-1</td></tr> <tr><td>5-1</td></tr> <tr><td>10-1</td></tr> <tr><td>20-1</td></tr> <tr><td>25-1</td></tr> <tr><td>50-1</td></tr> <tr><td>100-1</td></tr> </table>	RESISTANCE (3, 4 or 5 digits)	2-1	5-1	10-1	20-1	25-1	50-1	100-1	<table border="1"> <tr><td>PACKAGING</td></tr> <tr><td>TAPE AND REEL</td></tr> <tr><td>T0 = 100 min., 100 mult.</td></tr> <tr><td>T1 = 1000 min., 1000 mult.</td></tr> <tr><td>T3 = 300 min., 300 mult.</td></tr> <tr><td>T5 = 500 min., 500 mult.</td></tr> <tr><td>TF = full reel 3000</td></tr> <tr><td>TS = 100 min., 1 mult.</td></tr> <tr><td>UF = TUBED</td></tr> </table>	PACKAGING	TAPE AND REEL	T0 = 100 min., 100 mult.	T1 = 1000 min., 1000 mult.	T3 = 300 min., 300 mult.	T5 = 500 min., 500 mult.	TF = full reel 3000	TS = 100 min., 1 mult.	UF = TUBED		
GLOBAL MODEL (4 or 5 digits)																								
ORNA (Tin/lead)																								
ORNTA (Lead (Pb)-free) (e3)																								
RESISTANCE (3, 4 or 5 digits)																								
2-1																								
5-1																								
10-1																								
20-1																								
25-1																								
50-1																								
100-1																								
PACKAGING																								
TAPE AND REEL																								
T0 = 100 min., 100 mult.																								
T1 = 1000 min., 1000 mult.																								
T3 = 300 min., 300 mult.																								
T5 = 500 min., 500 mult.																								
TF = full reel 3000																								
TS = 100 min., 1 mult.																								
UF = TUBED																								
Historical Part Number Example: ORNA2-1 (for reference purposes only)																								
<table border="1"> <tr><td>ORNA2-1</td></tr> </table>	ORNA2-1	<table border="1"> <tr><td>2:1</td></tr> </table>	2:1	<table border="1"> <tr><td>10K</td></tr> </table>	10K	<table border="1"> <tr><td>5K</td></tr> </table>	5K	<table border="1"> <tr><td>2</td></tr> </table>	2															
ORNA2-1																								
2:1																								
10K																								
5K																								
2																								
PART NUMBER	DIVIDER NETWORK	R ₁ VALUE	R ₂ VALUE	R ₁ /R ₂ RATIO																				



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.