



Super Tek Travs with Wire Frames



Features

- Trays include a steel wire frame or conductive plastic corners, that can stack and nest together for more efficient use of space and more productive when moving product
- · Steel wire frames and conductive plastic corners provide improved durability and stability
- Great container for Kanban
- · Permanently static dissipative foam laminated to our impreganted corrugated material provides ESD and shock protection

Foam Electrical Properties: 1 x 10⁴ to < 1 x 10¹¹ ohms ANSI/ESD STM11.11

Foam Thickness: 1/8" (+/- 1/16" tolerances)

Item	Size I.D L x W x D (IN)
37760	18 x 11-3/8 x 1-3/4 with wire frames
37761	22-3/4 x 17-1/2 x 2-1/2 with wire frames
37762	18 x 11-3/8 x 1-3/4 with plastic corners
37763	22-3/4 x 17-1/2 x 2-1/2 with plastic corners

Dimensional tolerances are +/- 1/8" unless otherwise specified

Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and worksurface standard ANSI/ESD S4.1

SPECIFICATIONS

Properties

Sloughing Test

Recyclability

Typical Values Surface Resistance 1×10^{6} to < 1×10^{9} ohms Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test. No conductive particles abrased from surface Complete recyclability of package

Test Procedures/Method

ANSI/ESD STM11.11 ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load Rockwell International Test Report of January 8, 1992 Rockwell International Test Report of January 8, 1992



RoHS. REACH. and Conflict Minerals Statement: See the Desco Industries ROHS, Reach and Conflict Minerals Statement Made in the Descoindustries.com/ROHS3.aspx United States of America Specifications and procedures subject to change without notice. See the Protektive Pak Limited Warranty SUPER TEK-TRAYS Protektivepak.descoindustries.com/Limited-Warranty.aspx PROTEKTIVE PAK TFKTIVF PAK DATE: 13520 MONTE VISTA AVENUE, CHINO, CA 91710 DRAWING NUMBER December PHONE (909) 627-2578 BURIED SHIELDING LAYER 37760 2024 ProtektivePak.com