



### Features

- Economical ESD protective product to replace high charging plastic trash cans
- Static dissipative, low charging dissipative surface
- Constructed with double sides, triple ends, and double thickness bottom for greater durability (Items [37810](#), [37811](#))
- Steel reinforcing frame provides additional strength and durability
- Conductive plastic handles provide ease of handling along with reliable ESD control path-to-ground
- Identified with ESD Protective Symbol (Ref: ANSI/ESD 8.1) (Items [37810](#), [37811](#))
- Easy assembly without the need for tape, glue, or staples (Items [37810](#), [37811](#), [37812](#), [37813](#))
- ESD protective liners also available
- Impregnated corrugated material; greater durability than coated or printed material
- Buried shielding layer minimizes sloughing and rub-off contamination
- Made from 100% recycled material, and is 100% recyclable

**Meets the required limits of ANSI/ESD S20.20, and Packaging standard ANSI/ESD S541.**

### SPECIFICATIONS

#### Properties

#### Surface Resistance

#### Sloughing Test

#### Recyclability

#### Typical Values

1 x 10<sup>6</sup> to < 1 x 10<sup>9</sup> ohms

Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.

No conductive particles abraded from surface

Complete recyclability of package

#### Test Procedures/Method

ANSI/ESD STM11.11

ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load

Rockwell International Test Report of January 8, 1992

Rockwell International Test Report of January 8, 1992

Item	Description (L x W x D)
<a href="#">37810</a>	Trash Receptacle 13-1/2 x 12 x 13-1/4, 9 gal., with wire frame & handles
<a href="#">37811</a>	Trash Receptacle 13-1/2 x 12 x 13-1/4, 9 gal., receptacle only
<a href="#">37812</a>	Trash Receptacle 22-7/8 x 12-7/8 x 32, 40 gal., with wire frame & handles
<a href="#">37813</a>	Trash Receptacle 22-7/8 x 12-7/8 x 32, 40 gal., receptacle only
<a href="#">37820</a>	Trash Liner/ 10 gal. 26 x 24, 1.5 mil thickness
<a href="#">37821</a>	Trash Liner/ 55 gal. 22 x 16 x 58, 1.5 mil thickness

*"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." (ESD Handbook TR 20.20 section 2.4)*



Made in the United States of America

Specifications and procedures subject to change without notice

### Protektive Pak<sup>®</sup> ESD Trash Receptacle

Unless otherwise noted, tolerance is ±10%



PROTEKTIVE PAK  
13520 MONTE VISTA AVENUE, CHINO, CA 91710  
PHONE (909) 627-2578  
[ProtektivePak.com](http://ProtektivePak.com)

DRAWING NUMBER  
37810

DATE:  
December  
2024