





The Wristband 4600 Series consists of an insulative exterior with conductive interior and metal male snap available in 4mm. Made of thermoplastic material, the Wristband 4600 Series is lightweight, low profile and makes contact with human skin, assuring employee acceptance while helping to ensure ease of use. The "zipper" style latching mechanism easily adjusts to most wrist sizes. Meets requirements of ANSI/ESD S20.20 and Wrist Strap standard ANSI/ESD S1.1, and meets EN 61340-5-1 and IEC 61340-4-6.

Specifications	Typical Value	Test Method
Material	Thermoplastic elastomer; copolyester	
Size	Adjustable, small/large, 1.7 to 2.6 in diameter (43.2 mm to 66 mm)	
Resistance Inside	< 1 x 10 ⁵ ohms	ANSI/ESD S1.1/ IEC 61340-4-6
Resistance Outside	> 1 x 10 ⁷ ohms	ANSI/ESD S1.1/ IEC 61340-4-6
Cleanable	Water/mild detergent or 10% isopropyl solution	
Snap	4mm	
Snap Release	< 2 lbs.	
Back Plate	Stainless Steel	

Item	Description
<u>4620</u>	Wristband with 4mm male snap
<u>4650</u>	Wrist Strap with 5' Coil Cord, 4mm male snap

U.S. Patent 6,256,847

Unless otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice.



4620/4650 ADJUSTABLE THERMOPLASTIC WRIST STRAP

926 JR Industrial Drive, Sanford, NC 27332 **WEB SITE**: StaticControl.com

PHONE: EAST: (919) 718-0000 | WEST: (909) 627-9634

DRAWING NUMBER 4620/4650 Oct 2024