

Vishay Custom Magnetics

Miniaturized Gate Drive Planar Transformers



ABSOLUTE MAXIMUM RATINGS										
PARAMETER	CONDITIONS	LIMITS	UNITS							
Dielectric withstand voltage	Drive to gate, 1 min	3750	V_{AC}							
	Gate to gate, 1 min 2500		V_{AC}							
Total power dissipation (1)	T _A = 25 °C	2.0	W							
Operating temperature (2)	Continuous	-55 to +125	°C							
Storage temperature	Continuous	-55 to +130	ပ္							
Frequency		100 to 500	kHz							
Size (L x W x H)		20.57 x 18.42 x 11.43	mm							
Terminals	Through-hole and surface-mount									

Note

- (1) Derate at 33.3 mW/°C above 25 °C
- (2) Derate drive level to 60 V/µs above 85°C

FEATURES RoHS*

- Deliver MOSFET / IGBT gate power and timing signals simultaneously
- Directly drive high side MOSFETs / IGBTs on busses up to 1200 V
- Excellent rise time, overshoot, and peak current characteristics
- 8 mm minimum creepage and clearance from drive to gates
- Low profile planar package
- LF and SM versions are RoHS-compliant
- Material categorization: for definitions of compliance please see <u>www.vishay.com/doc?99912</u>

Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details


STANDARD ELECTRICAL SPECIFICATIONS											
PART NUMBER	USEFUL FREQ. RANGE (kHz) TRANSFER RATIO (± 3 %) (1)		DRIVE EXCITATION MAX. (Vµs)	MAGNETIZING INDUCTANCE MIN. (µH) ⁽²⁾⁽³⁾	LEAKAGE INDUCTANCE MAX. (µH) ⁽⁴⁾	DC RESISTANCE (2)		INTERWINDING CAPACITANCE			
						DRIVE MAX. (Ω)	GATES MAX. (Ω)	DRIVE TO GATE MAX. (pF)	GATE TO GATE MAX. (pF)		
MGDT100100	100 to 500	1:1:1	80	240	0.5	0.35	0.35	15	10		
MGDT100100LF	100 to 500	1:1:1	80	240	0.5	0.35	0.35	15	10		
MGDT100100-SM	100 to 500	1:1:1	80	240	0.5	0.35	0.35	15	10		
MGDT100125	100 to 500	1:1.25:1.25	80	240	0.5	0.35	0.50	25	10		
MGDT100125LF	100 to 500	1:1.25:1.25	80	240	0.5	0.35	0.50	25	10		
MGDT100125-SM	100 to 500	1:1.25:1.25	80	240	0.5	0.35	0.50	25	10		

Notes

- (1) Drive : gate : gate
- (2) $T_A = 25 \, ^{\circ}C$
- (3) 100 mV at 100 kHz across the drive winding with all gates open
- (4) 100 mA at 100 kHz into the drive winding with all gates shorted



Vishay Custom Magnetics





Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

© 2024 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED