



- Dual bands are switchable
- Low power consumption
- Higher reliability from integrated design principle
- Compact size and light weight
- Meet ETSI, FCC standards



## Block Downconverter C-Band 310 (BDC)

Model: GBDC3105, GBDC31010, GBDC31025

### Specifications

Parameter	Specification
Input Freq.	3.4 - 4.2 GHz
Output Freq.	950 - 1750MHz
L.O Freq.	5.15 GHz
Noise figure	10 dB max
Conversion gain at -40 to +60°C	40 dB typ. (37dB min. 43dB max.)
Gain flatness	4 dBp-p max.
Gain flatness at -40 to +60°C	5 dBp-p max.
Gain ripple at per 27MHz, -30 to +60°C	1 dBp-p max.
L.O stability at -40 to +60°C	±5, 10, 25 KHz max.
Image rejection	45 dBc min.
Phase noise	-73 dBc/Hz (@ 1KHz) -83 dBc/Hz (@ 10KHz) -93 dBc/Hz (@ 100KHz)
Output P1dB	+5 dBm min.
Input VSWR	2.0: 1 max
Output VSWR	2.0: 1 max
Input connector	SMA-type female
Output connector	F, N, SMA-type female (option)
Power supply	+12 to +24V DC
Power supply connector	Feed thru and/or output connector
Required current	300 mA max.
Operating temperature	-40 to +60°C

Continued on the next page ▼

